



Rocky Flats Environmental Technology Site

RECONNAISSANCE LEVEL CHARACTERIZATION

RADIOLOGICAL CHARACTERIZATION PLAN

GROUP 11 CLOSURE PROJECT


(T690N, 827, 850, C865, 881C South, 881C East, 881G, 881H, 881 Tunnel, 883C, & 890)

REVISION 0

November 20, 2001

Prepared by:  Date 11/19/01
Jay Bitten, Radiological Engineer

Reviewed by:  Date 11/20/01
Duane Parsons, Facility Characterization Coordinator

Reviewed by:  Date 11/26/01
Paul Miles, Quality Assurance

Approved by:  Date 11/26/01
Kent Dorr, Closure Project Facility Manager



Notes and Assumptions:

- This characterization Plan was prepared in accordance with MAN-077-DDCP, D&D Characterization Protocols (07/26/00), and MAN-127-PDSP, Pre-Demolition Survey Plan for D&D Facilities (02/14/01)
- PDSP Data Quality Objectives were used to develop this characterization plan

Instructions:

- 1 Verify characterization activities are on the Plan-of-the-Day (POD)
- 2 Perform a Pre-Evolution Brief and/or Job Task Brief in accordance with the Site Conduct of Operations Manual
- 3 Verify personnel have appropriate training for the applicable tasks they will be performing
- 4 Comply with RWP requirements, if applicable
- 5 Comply with JHA and facility PPE requirements, as applicable
- 6 Inform the Facility Manager, or designee prior to starting characterization activities
- 7 Follow applicable characterization and sampling procedures
- 8 Notify Wackenhut Security (x2444) and the Shift Supervisor (x2914), and verify appropriate safety precautions/requirements are followed prior to accessing facility roofs
- 9 Coordination with the Environmental Restoration Program organization will be required to further characterize underneath facility foundations and slabs prior to removal
- 10 Collect and maintain all characterization paperwork in the Project File(s)
- 11 All radiological surveys shall be conducted in accordance with the sampling and instruction forms included in Group 11 Survey Package numbers GR11-A-001, GR11-A-002, GR11-A-003 and GR11-B-004, GR11-A-005, GR11-A-006, GR11-A-007, GR11-A-008, GR11-B-009, GR11-A-010, GR11-A-011, & GR11-A-012 Sample locations are denoted on scaled maps attached to each survey package

Non-Impacted Areas										
N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	No Non-Impacted Areas identified in this characterization unit. Historical Site Assessment and process knowledge indicate no need for this classification
Non-Impacted Totals										

Class 1 Areas										
N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	No Class 1 Areas identified in this characterization unit. Historical Site Assessment and process knowledge indicate no need for this classification
Class 1 Totals										

Class 2 Areas										
N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	No Class 2 Areas identified in this characterization unit. Historical Site Assessment and process knowledge indicate no need for this classification
Class 2 Totals										

Class 3 Areas

A	G11-A-001	3	T690N (Interior & Exterior)	1281	563	65	15-random 15-biased 2-QC	15-random 15-biased	0	Areas are not expected to contain, or have ever contained, any residual radioactivity greater than the DCGLw. Historical Site Assessment and process knowledge of this unit provide a high degree of confidence that no individual measurement will exceed the DCGLw. A 5% scan on interior & exterior surfaces will be biased towards areas of greatest potential for contamination. Additional biased measurements have been prescribed and will be collected to ensure uniform coverage of all building surfaces. These additional biased measurements are above and beyond requirements set forth in the RFETS PDSP
A	G11-A-002	3	827 (Interior & Exterior)	321	78	17	15-random 10-biased 2-QC	15-random 10-biased	0	Areas are not expected to contain, or have ever contained, any residual radioactivity greater than the DCGLw. Historical Site Assessment and process knowledge of this unit provide a high degree of confidence that no individual measurement will exceed the DCGLw. A 5% scan on interior & exterior surfaces will be biased towards areas of greatest potential for contamination. Additional biased measurements have been prescribed and will be collected to ensure uniform coverage of all building surfaces. These additional biased measurements are above and beyond requirements set forth in the RFETS PDSP

Biased measurement locations include high traffic areas such as building entrances, exits, and hallways, HVAC intakes and exhaust ducts, storage areas, areas of frequent personnel contact such as doors and door frames, and horizontal surfaces

Class 3 Areas

A	G11-A-003	3	B850 (Interior)	11622	3038	349	46-random 64-biased 6-QC	46-random 64-biased	0	Areas are not expected to contain, or have ever contained, any residual radioactivity greater than the DCG _{LW} . Historical Site Assessment and process knowledge of this unit provide a high degree of confidence that no individual measurement will exceed the DCG _{LW} . A 3% scan on interior surfaces will be biased towards areas of greatest potential for contamination. Additional biased measurements have been prescribed and will be collected to ensure uniform coverage of all building surfaces. These additional biased measurements are above and beyond requirements set forth in the RFETS PDSP
B	G11-B-004	3	B850 (Exterior)	4002	2036	120	31-random 9-biased 2-QC	31-random 9-biased	0	Areas are not expected to contain, or have ever contained, any residual radioactivity greater than the DCG _{LW} . Historical Site Assessment and process knowledge of this unit provide a high degree of confidence that no individual measurement will exceed the DCG _{LW} . A 3% scan on exterior surfaces will be biased towards areas of greatest potential for contamination. Additional biased measurements have been prescribed and will be collected to ensure uniform coverage of all building surfaces. These additional biased measurements are above and beyond requirements set forth in the RFETS PDSP

Biased measurement locations include high traffic areas such as building entrances, exits, and hallways, HVAC intakes and exhaust ducts, storage areas, areas of frequent personnel contact such as doors and door frames, and horizontal surfaces

5

Class 3 Areas

A	G11-A-005	3	C865 (Exterior)	88	N/A	5	15-random 2-QC	15-random	0	Areas are not expected to contain, or have ever contained, any residual radioactivity greater than the DCGLw. Historical Site Assessment and process knowledge of this unit provide a high degree of confidence that no individual measurement will exceed the DCGLw. A 5% scan on interior & exterior surfaces will be biased towards areas of greatest potential for contamination. Additional biased measurements have been prescribed and will be collected to ensure uniform coverage of all building surfaces. These additional biased measurements are above and beyond requirements set forth in the RFETS PDSP. PDS Surveys are being conducted on the exterior surfaces of C865 only. Interior surfaces will be characterized using the Release Evaluation process during demolition.
A	G11-A-006	3	881C SOUTH (Exterior)	138	N/A	7	15-random 2-QC	15-random	0	Areas are not expected to contain, or have ever contained, any residual radioactivity greater than the DCGLw. Historical Site Assessment and process knowledge of this unit provide a high degree of confidence that no individual measurement will exceed the DCGLw. A 5% scan on interior & exterior surfaces will be biased towards areas of greatest potential for contamination. Additional biased measurements have been prescribed and will be collected to ensure uniform coverage of all building surfaces. These additional biased measurements are above and beyond requirements set forth in the RFETS PDSP. PDS Surveys are being conducted on the exterior surfaces of 881C only. Interior surfaces will be characterized using the Release Evaluation process during demolition.

Biased measurement locations include high traffic areas such as building entrances, exits, and hallways, HVAC intakes and exhaust ducts, storage areas, areas of frequent personnel contact such as doors and door frames, and horizontal surfaces

6

Class 3 Areas

A	G11-A-007	3	881C EAST (Exterior)	118	N/A	6	15-random 2-QC	15-random	0	Areas are not expected to contain, or have ever contained, any residual radioactivity greater than the DCGL _w . Historical Site Assessment and process knowledge of this unit provide a high degree of confidence that no individual measurement will exceed the DCGL _w . A 5% scan on interior & exterior surfaces will be biased towards areas of greatest potential for contamination. Additional biased measurements have been prescribed and will be collected to ensure uniform coverage of all building surfaces. These additional biased measurements are above and beyond requirements set forth in the RFETS PDSP. PDS Surveys are being conducted on the exterior surfaces of 881C only. Interior surfaces will be characterized using the Release Evaluation process during demolition.
A	G11-A-008	3	881G & 881H (Interior)	804	200	41	15-random 15-biased 2-QC	15-random 15-biased	0	Areas are not expected to contain, or have ever contained, any residual radioactivity greater than the DCGL _w . Historical Site Assessment and process knowledge of this unit provide a high degree of confidence that no individual measurement will exceed the DCGL _w . A 5% scan on interior & exterior surfaces will be biased towards areas of greatest potential for contamination. Additional biased measurements have been prescribed and will be collected to ensure uniform coverage of all building surfaces. These additional biased measurements are above and beyond requirements set forth in the RFETS PDSP.

Biased measurement locations include high traffic areas such as building entrances, exits, and hallways, HVAC intakes and exhaust ducts, storage areas, areas of frequent personnel contact such as doors and door frames, and horizontal surfaces

Class 3 Areas

B	G11-B-009	3	881G & 881H (Exterior)	724	292	37	15-random 10-biased 2-QC	15-random 10-biased	0	Areas are not expected to contain, or have ever contained, any residual radioactivity greater than the DCGLw. Historical Site Assessment and process knowledge of this unit provide a high degree of confidence that no individual measurement will exceed the DCGLw. A 5% scan on interior & exterior surfaces will be biased towards areas of greatest potential for contamination. Additional biased measurements have been prescribed and will be collected to ensure uniform coverage of all building surfaces. These additional biased measurements are above and beyond requirements set forth in the RFETS PDSP
A	G11-A-010	3	881 Tunnel (Interior)	623	135	32	15-random 5-biased 2-QC	15-random 5-biased	0	Areas are not expected to contain, or have ever contained, any residual radioactivity greater than the DCGLw. Historical Site Assessment and process knowledge of this unit provide a high degree of confidence that no individual measurement will exceed the DCGLw. A 5% scan on interior & exterior surfaces will be biased towards areas of greatest potential for contamination. Additional biased measurements have been prescribed and will be collected to ensure uniform coverage of all building surfaces. These additional biased measurements are above and beyond requirements set forth in the RFETS PDSP

Biased measurement locations include high traffic areas such as building entrances, exits, and hallways, HVAC intakes and exhaust ducts, storage areas, areas of frequent personnel contact such as doors and door frames, and horizontal surfaces

Class 3 Areas

A	G11-A-011	3	883C (Exterior)	118	N/A	6	15-random 2-QC	15-random	0	Areas are not expected to contain, or have ever contained, any residual radioactivity greater than the DCGLw. Historical Site Assessment and process knowledge of this unit provide a high degree of confidence that no individual measurement will exceed the DCGLw. A 5% scan on interior & exterior surfaces will be biased towards areas of greatest potential for contamination. Additional biased measurements have been prescribed and will be collected to ensure uniform coverage of all building surfaces. These additional biased measurements are above and beyond requirements set forth in the RFETS PDSP. PDS Surveys are being conducted on the exterior surfaces of 883C only. Interior surfaces will be characterized using the Release Evaluation process during demolition.
A	G11-A-012	3	890 (Interior & Exterior)	179	58	9	15-random 2-QC	15-random	0	Areas are not expected to contain, or have ever contained, any residual radioactivity greater than the DCGLw. Historical Site Assessment and process knowledge of this unit provide a high degree of confidence that no individual measurement will exceed the DCGLw. A 5% scan on interior & exterior surfaces will be biased towards areas of greatest potential for contamination. Additional biased measurements have been prescribed and will be collected to ensure uniform coverage of all building surfaces. These additional biased measurements are above and beyond requirements set forth in the RFETS PDSP.
Class 3 Totals				20018	6400	694	355	355	0	
All Class Areas			All Class Totals	20018	6400	694	355	355	0	

* Biased measurement locations include high traffic areas such as building entrances, exits, and hallways, HVAC intakes and exhaust ducts, storage areas, areas of frequent personnel contact such as doors and door frames, and horizontal surfaces

9/9